

PRODUCT DATA SHEET



RDE XTRA PLUS (DIESEL ENGINE OIL)

Introduction:

Motorol RDE XTRA PLUS 20W-40 is specially blended with friction modifier and other performance additives for heavy duty, commercial vehicles, trucks, LCVs, Vans, SUVs like Sumo, bolero, safari, etc. Suitable for latest 4 stroke diesel engines of turbo-charged and naturally aspirated type.

Applications:

- All new generation Turbo charged diesel engines.
- Commercial road transport vehicles of reputed OEMs
- Recommended for various on/off highway equipments.

Advantages:

- Increases engine life
- Reduces oil consumption
- Reduces maintenance cost
- Provides smoother operation & greater mileage

e

Performance Standard:

API CF4, MACK T-8A

Typical Specifications:

Sr. No.	Characteristics	Test Method	Typ. Value
1	Appearance	VISUAL	Bright & Clear
2	Colour, Max	VISUAL	Red
3	Kinematic Viscosity at 100°C, cSt	ASTM D - 445	13.5 - 15.5
4	Viscosity Index, Min	ASTM D - 2270	110
5	TBN, mg KOH/g	ASTM D - 2896	8-10
6	Flash Point, (COC), °C Min	ASTM D - 92	210
7	Pour Point, °C Max	ASTM D - 97	(-) 21

Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request.

MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not Spill oils on the shop floor, discharge into drains ,ground or water sources.



Plot No. 85/B-115, At-Post Karakhadi, Taluka: Padra, District: Baroda—391450, Gujarat, India Contact No: +91-2662-273373, 273727 Fax No: +91-2662-273720 Website: www.quebecoils.com Email: sales@quebecoils.com