




**RDE XTRA (DIESEL ENGINE OIL)**



**Introduction:**

Motorol RDE XTRA 20W-40 is specially blended with high VI modifier and other performance additives for Heavy duty commercial vehicles, trucks, LCVs, Vans, SUVs like Sumo, Bolero, Safari, etc.

**Applications:**

- ◆ All new generation Turbo charged diesel engines.
- ◆ Commercial road transport vehicles of reputed OEMs
- ◆ Recommended for various on/off highway equipments.

**Advantages:**


- ◆ Increases engine life
- ◆ Reduces oil consumption
- ◆ Reduces maintenance cost
- ◆ Provides smoother operation & greater mileage

**Performance Standard:**

API CD/SF, MACK T-8A

**Typical Specifications:**

| Sr. No. | Characteristics                   | Test Method   | Typ. Value     |
|---------|-----------------------------------|---------------|----------------|
| 1       | Appearance                        | VISUAL        | Bright & Clear |
| 2       | Colour, Max                       | VISUAL        | Red            |
| 3       | Kinematic Viscosity at 100°C, cSt | ASTM D - 445  | 13.5 - 15.5    |
| 4       | Viscosity Index, Min              | ASTM D - 2270 | 110            |
| 5       | TBN, mg KOH/g                     | ASTM D - 2896 | 6-8            |
| 6       | Flash Point, (COC), °C Min        | ASTM D - 92   | 210            |
| 7       | Pour Point, °C Max                | ASTM D - 97   | (-) 21         |



**Environment, Health & Safety:**

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request.

MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not Spill oils on the shop floor, discharge into drains ,ground or water sources.