

PRODUCT DATA SHEET



MAGIC 4T GOLD (4 STROKE TWO WHELLER ENGINE OIL)

Introduction:

Motorol MAGIC 4T GOLD is unique premium lubricant blended with superior high viscosity index base oil & versatile additive technology. Recommended for 4 stroke engines of modern motorcycles. Specially designed and formulated to ensure longer life of engines, clutch & gear components. This Oil meets (VTW) valve train wear of API SM of SAE 20W-40.

Applications:

- All new generation 4 stroke two wheeler engine of reputed OEMs.
- Recommended for 4 stroke two wheelers like Hero Honda, Bajaj Auto, TVS, Yamaha, Kinetic, LML, Honda, etc.

Advantages:

- Highly shear stable.
- Lower high temperature deposits
- Lower oil consumption
- Prevents clutch slippage at varying speeds

e

1000

Catalytic convertor compatible

Performance Standard:

• API SL, JASO MA2

Typical Specifications:

Characteristics	Test Method	Typ. Value
Appearance	VISUAL	Bright & Clear
Colour, Max	ASTM D 1500	3
Kinematic Viscosity at 100°C, cSt	ASTM D - 445	13.5-15.5
Viscosity Index, Min	ASTM D - 2270	110
TBN, mg KOH/g	ASTM D - 2896	5-7
Flash Point, (COC), °C Min	ASTM D - 92	210
Pour Point, °C Max	ASTM D - 97	(-) 21
	AppearanceColour, MaxKinematic Viscosity at 100°C, cStViscosity Index, MinTBN, mg KOH/gFlash Point, (COC), °C Min	AppearanceVISUALColour, MaxASTM D 1500Kinematic Viscosity at 100°C, cStASTM D - 445Viscosity Index, MinASTM D - 2270TBN, mg KOH/gASTM D - 2896Flash Point, (COC), °C MinASTM D - 92

Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request.

MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not Spill oils on the shop floor, discharge into drains ,ground or water sources.



Plot No. 85/B-115, At-Post Karakhadi, Taluka: Padra, District: Baroda—391450, Gujarat, India Contact No: +91-2662-273373, 273727 Fax No: +91-2662-273720 Website: www.quebecoils.com Email: sales@quebecoils.com